

Product Information ÖKO 6


Electronic starter for 4-125W single fluorescent lamp circuits.

The soft start system utilised in the ÖKO 6 electronic starter first pre-heats the lamp cathodes to working temperature, before applying a controlled voltage pulse to strike the arc. This method of ignition prevents cathode damage and significantly lengthens lamp life. Additionally, a safety monitoring system shuts down the system in the event of a fault and prevents dangerous overheating and the annoying flashing associated with glow type starters. Refined circuit methods allow us to provide a 10 year no quibble guarantee for this product which has a proven design life exceeding 20 years.

Housed in a two - pin canister with dimensions in accordance to IEC155, for the direct replacement of glow starters without circuit modification.

Dimensions & materials:

Canister: Polycarbonate, translucent green
 Printing: Silver
 Base: Polycarbonate
 Pins: Nickel plated brass



All dimensions in millimetres

Technical Data:

Operating voltage:	200 - 250 V AC 50/60 Hz
Preheat time:	2.3 seconds nominal @ 20 C
Pulse height:	1500 V maximum
Safety shutdown:	Within 3 seconds @ 20 C
Lamp types:	4-125W Linear T5/T8/T12 (not 100W 2.400mm) 10-38W 2D (TC-DD) 11W PLS (TC) 10-26W PLC (TC-D) 18-36W PLL (TC-L) 20-60W Circular and U Tube (T-R, T-U)
Operating temperature:	- 20 to + 100 C
Storage temperature:	- 50 to + 105 C

Approvals:



N15397

